

ULTRA MINIATURE SMD HCMOS OSCILLATOR (2.0 x 1.6 x 0.9mm)

FEATURES:



- WIDE FREQUENCY RANGE
- LOW VOLTAGE / LOW CURRENT
- ENABLE / DISABLE



■ SPECIFICATION

FREQUENCY RANGE		1.000MHz ~ 60.000MHz		1.000MHz ~ 80.000MHz
FREQUENCY STABILITY		±25ppm ~ ±100ppm		
OPERATING TEMPERATURE RANGE		STD: 0°C ~ 70°C, Option: -40°C ~ 85°C (See P/N guide for other options)		
STORAGE TEMPERATURE RANGE		-55°C ~ 125°C		
SUPPLY VOLTAGE ±10%		1.8V _{DC}	2.5V _{DC}	3.3V _{DC}
SUPPLY CURRENT	1MHz ≤ f ≤ 10MHz:	0.4mA typ.	2.0mA typ.	2.0mA typ.
	10MHz < f ≤ 20MHz:	1.0mA typ.	2.0mA typ.	2.0mA typ.
	20MHz < f ≤ 25MHz:	1.0mA typ.	2.0mA typ.	3.0mA typ.
	25MHz < f ≤ 50MHz:	2.0mA typ.	4.0mA typ.	3.0mA typ.
	50MHz < f ≤ 60MHz:	-	4.0mA typ.	5.0mA typ.
OUTPUT	LOGIC FAMILY	HCMOS		
	LOAD	15pF		
	LEVEL LOGIC '1' (V _{OH})	0.9 x V _{DD} min.		
	LEVEL LOGIC '0' (V _{OL})	0.1 x V _{DD} max.		
	SYMMETRY(DUTY CYCLE)	STD: 40% / 60% @ 1/2V _{DD} level, Option: 45% / 55%		
	RISE AND FALL TIME (Tr/Tf)	3.0nS typ. 10nS max.		
	START-UP TIME	10mS max.		
STAND-BY VOLTAGE	ENABLE (V _{IH})	0.7 x V _{DD} ≤ V _{IH} ≤ V _{DD} or N/C		
	DISABLE (V _{IL})	V _{IL} ≤ 0.3 x V _{DD}		
ENABLE DELAY TIME		10mS max.		
DISABLE DELAY TIME		10mS max.		
AGING @ 25°C ± 3°C		±3.0ppm / 1 st year max.		
PHASE JITTER RMS (12kHz ~ 20MHz)		1.0pS max.		


■ PACKAGE DIMENSIONS



Unit : mm


Pin Configuration	
1	En/Dis
2	GND
3	Output
4	V _{DD}

■ SOLDER PATTERN



*0.01μF to 0.1μF bypass capacitor recommended

■ REFLOW PROFILE



Note: Consult factory for detail

■ PART NUMBERING GUIDE

TSM21 - H 50 HM 33 S T - 12.000M - TR									
Product series		Output		Stability		Symmetry		Tape and Reel	
H: HCMOS		00: ± 100ppm 50: ± 50ppm 25: ± 25ppm XX: Two digit for Stability		R: 40/60% S: 45/55%		TR: 3000/reel Blank: Cut tape		Frequency	
								M: MHz	
								Tristate	
								T: En/Disable N: N/C	
								Supply Voltage	
								18: 1.8 Volt 25: 2.5 Volt 33: 3.3 Volt	

Operating Temperature

A: -55	F: -20	M: 70	S: 100
B: -50	G: -10	N: 75	T: 105
C: -40	H: 0	P: 80	U: 125
D: -35	J: 50	Q: 85	X: custom
E: -30	K: 60	R: 90	

Transko Electronics, Inc reserves the right to make changes to the product (s), service (s), and specification (s) described herein without notice. See "Terms of Sale" for details on our website.