

Table 1. Electrical Performance

| Parameter | Symbol | Min. | Typ | Max | Units |
|-------------------------------------|------------|------------------------------|-----|---------|-------|
| Nominal Frequency | F_{NOM} | 1.8432 | | 150.000 | MHz |
| Mode | | Fundamental, 3rd Overtone | | | |
| Operating Temperature Range | T_{OP} | 0/70, -10/70, -20/70, -40/85 | | | °C |
| Stability Over T_{OP}^1 | F_{STAB} | ±10 | | ±100 | ppm |
| Frequency Tolerance ² | F_{TOL} | | ±10 | | ppm |
| Load Capacitance | C_L | 6 | | 32 | pF |
| Shunt Capacitance | C_o | | | 5 | pF |
| Drive Level | | | 10 | 100 | uW |
| Aging / 1st year (at 25 °C) | F_{AGE} | | | ±5 | ppm |
| Insulation Resistance | | 500 | | | MOhm |
| Storage Temperature | T_{STO} | -40 | | 90 | °C |
| Equivalent Series Resistance | | | | | |
| Crystal Frequency | ESR | | | | Ohm |
| 1.536MHz-2.000MHz | | | | 500 | |
| 2.001MHz-2.456MHz | | | | 450 | |
| 2.457MHz-3.000MHz | | | | 350 | |
| 3.001MHz-4.000MHz | | | | 90 | |
| 4.001MHz-5.000MHz | | | | 70 | |
| 5.001MHz-8.000MHz | | | | 60 | |
| 8.001MHz-10.000MHz | | | | 30 | |
| 10.001MHz-50.000MHz, fundamental | | | | 25 | |
| 24.000MHz-150.000MHz, 3rd Overtone | | | | 40 | |

Notes:

1. Referenced to the Frequency at 25 °C.

2. Frequency measured at 25 °C ± 3 °C.

Product is compliant to RoHS directive and fully compatible with lead free assembly. 

Package Drawing

